

# Data Sheet

## FUJITSU Storage ETERNUS HB1100



### ETERNUS HB

FUJITSU Storage ETERNUS HB series is NVMe ready hybrid storage systems with performance and efficiency of block storage systems helping drive business value at a reduced cost. The ETERNUS HB is built for optimized for integration into existing business critical workloads like Microsoft SQL server, Oracle, SAP, etc. In addition to enhanced data protection features, a variety of APIs (REST-based), orchestration tools (Ansible), and plug-ins (Splunk, Nagios) are available for managing/monitoring HB Series systems.

### ETERNUS HB1100

The ETERNUS HB1100 storage system is ideal for small sized businesses, plus enterprise remote and branch offices with limited hardware expansion and software features. ETERNUS HB1100 offers hybrid SSD and HDD configurations and allows you to gain insights quickly, simply and affordably from a range of mixed workload environments, including data analytics, video surveillance and high performance computing.



# Features & Benefits

Main Features	Benefits
Accelerates Business Applications	<ul style="list-style-type: none"><li>■ Higher performance with solid-state drives (SSDs) enables the ETERNUS HB1100 to maximize storage density, requiring fewer disks to meet your performance objectives.</li><li>■ Streamline your IT infrastructure and drive down costs</li><li>■ Secondary cache feature provides intelligent analytics-based caching capabilities for read intensive workloads</li></ul>
Continuous availability	<ul style="list-style-type: none"><li>■ ETERNUS HB1100 storage systems enable you to achieve greater than 99.9999% availability and provide data integrity and security</li><li>■ validates data integrity and protects against silent data corruption</li><li>■ All management tasks are carried out while the storage remains online with complete read/write data access. Storage administrators can make configuration changes and conduct maintenance without disrupting application I/O.</li><li>■ Background monitoring proactively scans media and tracks drive health against defined thresholds.</li></ul>
Flexible configuration Options	<ul style="list-style-type: none"><li>■ Enables the automation and agility that are needed in the DevOps-based IT revolution</li><li>■ The ultradense 60-drive system shelf supports up to 720TB in just 4U and is optimal for environments with vast amounts of data and limited floor space, with either 2.5-inch or 3.5-inch drives.</li><li>■ Industry leading performance and space efficiency to reduce rack space by up to 60%. Its high-efficiency power supplies can lower power and cooling use by up to 40%.</li></ul>

# Technical details

## General system information

	Base
No. of controllers	2
No. of host interfaces	4 Port [FC (4, 8, 16Gbit/s)] 4 Port [iSCSI (10Gbit/s)] 4 Port [iSCSI (10GBase-T)]
Maximum System Memory	16 GB
Maximum Disk Drives	24
Max. no. of drive enclosures	1
Supported RAID levels	0, 1, 1+0, 3, 5, 6, DDP
Host Interfaces	FC (4, 8, 16Gbit/s) iSCSI (10 Gbit/s, 10 GBASE-T)
Mixed host interfaces	No
Max. no. of hosts	128
Maximum Storage Capacity	432 TB
Maximum Storage Capacity HDD	432 TB
Maximum Storage Capacity SSD	12.8 TB
Drive Type	3.5-inch, Nearline SAS, 7.2krpm (18TB / 16TB / 12TB / 8TB / 4TB) 3.5-inch, Nearline SAS (FIPS), 7.2krpm (10TB) 3.5-inch, SSD (800GB) 3.5-inch, SSD (FIPS) (1.6TB)
Max. no. of SSDs	8
Drive interface	12G SAS(MiniSAS HD)
Back-end disk connectivity	2/Controller
Max. no. of RAID groups per system	24
Max. no. of LUNs per RAID group	256
Max. no. of LUNs	256
Max. LUN capacity	2 PiB
Max. no. of copy generations	128

## Performance management

Operation Management Client	Google Chrome 47, Microsoft Internet Explorer 11, Microsoft Edge EdgeHTML 12, Mozilla Firefox 31, Safari 9
-----------------------------	--

## Continuity management

Remote Copy functionality	Asynchronous(Optional)
---------------------------	------------------------

## Information security management

Data confidentiality	HTTPS (SSL), SSH, iSCSI (CHAP, Bidirectional CHAP)
Data integrity	Replace drive logically, Rebuild (DDP Rebuild, hot spare converge works), Cache Protection (Backup method, Backup data, Backup retention time: No limit), Data Encryption (Self encryption disk), Media scan, Data Assurance, T10-PI, Check Volume Redundancy

## Availability management

Non-disruptive firmware upgrade	Yes
Hot part replacement	Yes

## Capacity management

Thin Provisioning	Yes
Reporting function	Yes (Performance, Capacity, host connectivity)
Hot part expansion	Yes
Non-disruptive firmware upgrade	Yes

## Management

Interfaces	1Gb Ethernet
------------	--------------

**Management**

Supported protocols	SNMP v2c, REST
Administration	SANtricity System Manager(GUI: Graphical user interface), SMCLI(CLI: Command Line Interface), REST API, SANtricity Unified Manager

**Supported OS for Management software**

Operation Management Client	Google Chrome 47 Microsoft Internet Explorer 11 Microsoft Edge EdgeHTML 12 Mozilla Firefox 31 Safari 9
-----------------------------	--

**Installation specification**

19" rackmount	Yes	
Power voltage	AC200V / AC100V	
Power frequency	50 / 60 Hz	
Maximum Power Consumption	AC200V / AC100V: Controller Shelf: 565W 2U-Drive Shelf: 344W	
Power phase	Single	
	Base	3.5 Drive Shelf
Dimensions (W x D x H)	480 x 505 x 87 mm 18.9 x 19.9 x 3.4 inch 2 U	480 x 505 x 87 mm 18.9 x 19.9 x 3.4 inch 2 U
Weight	28.8 kg (63 lb)	28.7 kg (63 lb)

**Environment**

Maximum Heat Generation	AC200V / AC100V: AC200 - 240V: 3273: kJ/h
Temperature (operating)	5 - 45 °C
Humidity (operating)	8 - 90 %

**Compliance**

Product safety	EN 60950-1, IEC 60950-1, CAN/CSA C22.2 No. 60950-1, ANSI/UL 60950-1, TP TC 004/2011, CNS14336-1
Electromagnetic Compatibility	EN55032, CISPR32, VCCI Class A, AS/NZS CISPR 22:2009+A1:2010, AS/NZS CISPR 32:2013, AS/NZS CISPR 32:2015, Class A, CNS 13438, TP TC 020/2011
Electromagnetic Immunity	EN 55032, CISPR32, VCCI Class A, AS/NZS CISPR 22:2009+A1:2010, AS/NZS CISPR 32:2013, AS/NZS CISPR 32:2015, Class A, CNS13438, TP TC 020/2011, KN32
Environmental compliance	RoHS compliant, WEEE compliant
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>

**Warranty**

Warranty period	3 years
Warranty type	Onsite warranty
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/warranty">www.fujitsu.com/warranty</a>

**Product Support Services - the perfect extension**

Service Lifecycle	5 years after end of product life
Service Weblink	<a href="http://www.fujitsu.com/services/product-services">www.fujitsu.com/services/product-services</a>

### Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS HB1100, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu ETERNUS HB1100, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2021 FUJITSU LIMITED

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

### Contact

FUJITSU LIMITED

Website: [www.fujitsu.com/eternus](http://www.fujitsu.com/eternus)

2021-07-30 WW-EN